

Deep Foundation Pit Excavations Adjacent to Disconnected Piled Rafts: A Review on Risk Control Practice

Bantayehu Uba Uge , Yuancheng Guo

School of Civil Engineering, Zhengzhou University, Zhengzhou, China

Email: bantayehuu@gs.zzu.edu.cn

How to cite this paper: Uge, B.U. and Guo, Y.C. (2020) Deep Foundation Pit Excavations Adjacent to Disconnected Piled Rafts: A Review on Risk Control Practice. *Open Journal of Civil Engineering*, 10, 270-300. <https://doi.org/10.4236/ojce.2020.103023>

Received: June 21, 2020

Accepted: September 21, 2020

Published: September 24, 2020

Copyright © 2020 by author(s) and Scientific Research Publishing Inc.

This work is licensed under the Creative Commons Attribution International License (CC BY 4.0).

<http://creativecommons.org/licenses/by/4.0/>



Open Access

Abstract

Foundation pit excavation engineering is an old subject full of decision making. Yet, it still deserves further research due to the associated high failure cost and the complexity of the geological conditions and/or the surrounding existing infrastructure around it. This article overviews the risk control practice of foundation pit excavation projects in close proximity to existing disconnected piled raft. More focus is given to geotechnical aspects. The review begins with achievements to ensure excavation performance requirements, and follows to discuss the complex soil structure interaction involved among the fundamental components: the retaining wall, mat, piles, cushion, and the soil. After bringing consensus points to practicing engineers and decision makers, it then suggests possible future research directions.

Keywords

Deep Foundation Pit Excavation, Disconnected Piled Raft Foundation, Risk Control, Observational Method

1. Introduction

Burgeoning intentions to use basement slabs as a component contributing to the foundation's bearing capacity and settlement requirements have recently spurred an escalated demand for piled-rafts as an economical alternative foundation system. The 828 m tall Burji Khalifa building in Dubai is an example founded on piles beneath the base of thick slab—the raft [1]. Moreover, raft foundations integrated with column type ground improvement (rigid inclusions) have widely been practiced in many parts of the world to utilize marginal urban soft ground [2]. In China, the columns are mainly constructed with ce-

ment-fly-ash-gravel (CFG) and the improved ground is termed as CFG pile composite foundation [3] [4] [5]. The 200 m high structure in Dalian City, China, for example, was built on composite foundation where the raft transfers the load from the superstructure to the ground treated by vertical columns [6]. This shows, based on the intended use, piles may be connected or disconnected to the raft. To circumvent localized higher stress and bending moment at the point of connection between the piles' head and the raft during lateral and seismic loads, an interposed layer of sufficient thickness is laid [7] [8]. Previous experimental and numerical analyses indicated that the disconnecting layer plays a significant role in distributing superstructure loads in such an interplay that integrates the piles and the soil in load sharing mechanism [9] [10]. In this case, the piles receive the upper load indirectly and mostly considered as stiffeners of the marginal ground or settlement reducers [11]. Many researches are now being done to understand the complex soil-structure interaction (SSI) phenomena in disconnected piled rafts [12] [13] [14] [15].

On the other hand, in recent years, the use of underground space has evidently become an important attribute to promote sustainable development [16] [17] [18]. In fact, aggressive progress towards underground construction will spate in a complex manner, with stringent performance requirement for deep foundation pit excavation support [19] [20] [21] [22]. The consequences of foundation pit excavation support's failures are significantly dangerous and risky, mandating proper monitoring during construction [23] [24] [25]. For example, the 2004's sudden collapse of Singapore's deep braced excavation of Mass Rapid Transit Circle Line project adjacent to Nicoll Highway was reported to result in a disaster in four fatalities, costing approximately \$6.7 billion [26]. The Chinese Hangzhou Metro Line 1 project collapse in 2008 was found to take 17 lives and other four missing, with more than ¥50 million loss [27]. Such catastrophic collapses affect the performance of the surrounding infrastructures; similar to the toppling of the 13-floor building in Minhang District of Shanghai, China causing huge social effects [28]. In 2009, the failure of deep excavation at the Cologne metro station in Germany was anticipated to be due to the increase in hydraulic gradient during the excavation, in turn the historical City Archive Building collapsed [29].

When neighboring structures or public utilities exist, the design and performance requirement of deep excavation project is met on the bases of serviceability rather than failure prevention criteria [20] [30]. The construction method must also be able to confirm practically that the induced ground movement is tolerable, so the subsequent associated risks are controlled. Previous research on the design and construction on deep foundation pit excavation works mainly focused on excavation pit support, related ground and wall movements, design and/or construction risks (see **Table 1**).

Regardless of whether the project is delivered by traditional Design-Bid-Build or Design-build bidding, the construction of deep foundation pit excavation is

Table 1. Selected researches on foundation pit excavation and the interaction with its surrounding.

Focus of study	Reference	Methodology	Key research parameter
Prediction of excavation-induced ground and wall movement	[31]	Numerical	Small-strain soil behavior
	[32]	Empirical + numerical	3D distribution of soil movements, small strain behavior of the soil
	[33]	Analytical	Plane strain problem, modes of wall displacement
	[34]	Numerical	Constitutive soil models, displacement of tieback wall
	[35]	Modified mobilizable strength design (MSD) method	Deformation of multipropped excavation, excavation geometries, strength mobilization characteristics of soil
	[36]	Numerical	Sheet pile wall installation, construction sequence and bracing
	[37]	Numerical	Diaphragm wall deflection, ground surface settlement, excavation depths, geological conditions
	[38]	Numerical	Narrow excavations, support stiffness, excavation width-depth ratio
	[39]	Numerical	Watertightness Assessment Test before excavation, stability of the bottom of the excavation, defects in the enclosure (gaps or open joints)
Effect of groundwater (GW) dewatering	[40]	State-of-the-art review	Ground settlement, interactions between the retaining wall-dewatering well, the dewatering-excavation, and dewatering-recharge
	[41]	Field observations	Wall deflection (diaphragm wall/secant-bored pile wall), ground surface settlement, stage of excavation, groundwater drawdown
	[42]	Case study	Dewatering (pumping rate and depth of a cutoff wall), soil properties, building settlement
	[43]	Review on water leak incidents	Water ingress (leak through joints & seepage-prone weak zone), surface settlements and diaphragm wall deflection
Design and support optimization	[44]	Robust geotechnical design (RGD)	Braced excavation, wall deflection, Cost-efficiency (costs of the diaphragm wall, the bracing system, excavation/disposal of the dirt, dewatering, and instrumentation)
	[45]	RGD coupled with first order second moment (FOSM) method	Braced excavation (geometry and depth), wall deflection, uncertainties of soil parameters (noise factors), cost efficiency, robustness and safety
	[46]	Constructing indicator system of optimization of supporting schemes based on TOPSIS	Technical feasibility, effect reliability (such as static and dynamic performances), construction accessibility (complexities during construction), economic rationality
	[47]	Numerical analysis	Bearing capacity, stability design requirements, and environmental requirements during construction, composite support systems, soil arching effect between existing pile foundations (bending moment in the piles)
	[48]	FEM for analysis, BS8081:1989 for ground anchor, BS8002:1994 for toe stability check, BS 5950 and CIRIA Special Publication 95 for strutting elements	Secant pile retaining wall, water-tightness, ability to vary the depth of retaining wall for irregular soil profiles, HS-Small model, grouting techniques, excavation support stability, assessment of surrounding infrastructure's damage

Continued

	[49]	Numerical inverse analysis	A shift from temporary to permanent support system, over-excavation (design depth increment), stress-strain behavior
	[50]	Divided-pit construction (FEM implemented)	Irregular excavation geometry and depth, displacement of adjacent conserved buildings (relative location from the pit), effects of buildings on excavation process (pit deformation due to buildings)
	[51] [52]	Zoned and staged construction, Channel-type top-down method of excavation	Construction cost and schedule, excavation support deformation, hauling distance, safe operation of adjacent railway (allowable displacement of the rail tracks)
	[53]	Dividing alternate excavation method (strip excavation plus several dividing walls)	Time-space effect and stiffness of tunnel, tunnel deformation, construction period
Construction method	[54]	Case histories from bottom-up construction technique	Foundation pit deformation, quick excavation, promptly propping, timely casting of floor slabs, segmented construction, excavation stage
	[55]	Top-down technique and inverse numerical analysis	Displacements of existing buildings, retaining wall deformations, hydraulic uplift failure mechanisms, wall installation effect
	[56]	Both top-down and bottom-up construction method with bipartition walls	Oversized excavation, time-space-effect on both deflection of diaphragm wall and deformation of partition walls
	[57]	Zoned excavation and instrumented observation	Wall deflection, ground settlement, corner effect, construction sequence, performance of adjacent metro line
	[58]	Bottom-up construction method with zoned construction	Lateral wall displacement, adjacent utility tunnel movement, stage and sequence of construction, construction schedule, groundwater dewatering, basal ground treatment
	[59]	Numerical	Excavation zone of influence, building settlement
	[60]	Numerical	Frame action with inclusion of building stiffness, limiting tensile strain
	[61]	Numerical	Stages of construction, deformation of excavation, strains of adjacent buildings
	[62]	Analytical	Excavation induced axial pile deformation, vertical soil displacement, load transfer mechanism
Interaction with the surrounding environment	[63]	Analytical	Tunnel deformation
	[41] [64] [65] [66]	Numerical	Effect of depth of excavation, supporting system stiffness, pile dimensions, pile head condition, working load, soil properties, location from excavation
	[67]	Numerical	Isolation piles and jet-grouted piles, displacement of retaining wall
	[68]	Numerical	Building deformations and settlement due to excavation, distance to excavation, type of building's foundation
	[69]	Numerical	3D structural distortion based on soil-structure interaction, damage due to differential displacement

Continued

Monitoring technology and early safety warning	[70]	Levelling, rod extensometers and torpedo inclinometer	Ground and wall displacements, accuracy of monitoring method (human or environmental errors)
	[71]	Internet-of-Things-(IoT) based safety barrier early warning system	Tracking of workers and “things” to change their risky behaviors, diaphragm wall collapse (elastic potential energy exceeded)
	[72]	Optical fiber sensing technology (fiber Bragg grating-FBG-technology)	Deformation of foundation pit
	[73]	Slope indicator systems, strain gauges, optical fiber and topographic survey	Displacements and strains of a noncontinuous anchored wall, earth pressure influence on lateral displacement (supported by numerical analysis)
	[74]	Displacement monitoring with a precise total station; crack measurements, rainfall observations, groundwater and seepage observations; Stress-monitoring equipment (vibrating string extensometer); Computer aided information management system	Deformation of foundation pit, ground surface settlement, inclination of the surrounding buildings, foundation settlement of adjacent buildings, integrated management of monitoring data (instrumentation, monitoring points, construction progress, the surrounding environment) and 3D visualization
Construction safety risk management	[75]	Numerical	Existing adjacent railway operation, railway subgrade deformation
	[76]	Monitoring based risk disposal	Distance from excavation, additional load due to stock piling materials on the pit edge, groundwater level change
	[77]	Case analysis of safety accidents (accident forecasting and prevention)	Safety behaviors of personnel, technological innovation of safety management, integration of networking and digital technology
	[78]	Support Vector Machine	Excavation deformation, longitudinal slope instability, gushing of water and sand
	[79]	Building Information Modeling (BIM)	Technical risks, Geological risks, Environmental risks
	[80]	Equivalent axial stiffness theory & Monte Carlo simulation technique	Soil parameter uncertainty, tunnel longitudinal stiffness, excavation depth
	[81]	Case study on damage remedial work	Grouting, soil unloading due to excavation, deformation of shield tunnel, groundwater drawdown

still fraught with challenges. It requires progressive monitoring of project performance. If deviations from design expectations are encountered during construction, appropriate modifications will be made and the experience gained can be used in a different way in the future [82]. This process usually takes five stages: Information, Analysis, Prediction, Observation and Evaluation [83]. Limited data, as well as the spatial variation of material properties involved in the complex geo-environment and unavailability of soil model to capture all aspects of material's behavior, have forced geotechnical engineers to rely on simplification and engineering judgment to fit analysis and prediction results [5] [34] [84]. This helped to develop presumed designs and safe constructability. Moreover, in the observation process, handling critical data requires more attention than the mechanics and manipulation of the data. Then, during evaluation process, the questions arising from the deviation between observed performance and ex-

pected performance will be answered. The results of the analysis will indicate the source of associated risks (hazards) and possible control measures to minimize/alleviate these risks. Therefore, a risk control process that accommodates the daily changes during construction is necessary for the successful completion of deep excavation pit project safely.

With this in mind, it becomes self-evident that the success of deep foundation pit excavation project is reflected on how it links the competence of project management process with risk-informed decision making. Besides, in the context of reasoned geotechnical judgment that systematically combines “data” and “experience”, it can succinctly be described that a pressing demand is currently prompted on the role of relevant data which explicitly takes uncertainties into account. Consequently, it is unlikely to possibly reduce taking heed to risks in the near future, especially when novel foundations systems emerge. At this point of departure, this paper enlightens the construction profession regarding geotechnical aspects of risk control and management practice for new foundation pit excavations near the recent widely used on-service disconnected piled rafts.

In what follows, the method for predicting the likelihood and occurrence of unintended events in the deep foundation pit excavation project adjacent to conventional foundation system is introduced first. Then, for space brevity, brief discussion in the context of disconnected piled raft is covertly provided under separate sections allocated to topics on how to confront uncertainties during risk prediction; risk control measures; and risk management process. Ultimately, as there always exists something to explore in any area of study, future research directions, at least to the level of this article, are forwarded for interested scholars. Since several parties are involved to partake decisions at different levels, final decision will be affected by a certain sources of bias among the stakeholders [85]. Geotechnical engineers are responsible to make clear geotechnical bias sources for better decision makings. Accordingly, this paper gives more attention to demonstrate geotechnical aspects; and organizes the challenges arising from direct or indirect risks for deep foundation pit excavations in close proximity to existing structures supported by disconnected piled rafts. The concepts discussed will help practicing engineers to resolve the impact of uncertainties in a well-organized and structured manner.

2. Risk Prediction Methods

Risk and decision are almost interrelated [86]. Many factors exist that cause risk associated with interconnected tasks for a given project. They result in time delay or cost overruns if not properly dealt with in the process of risk management. Risk management mainly includes risk identification, analysis and response. In order to take effective counter measures to deal with the impact of risks, project managers or decision makers should implement strategies. The approach to do so is to measure the expected loss due to risk based on the potential impact and occurrence probability [87] [88] [89] [90]. For projects like deep foundation pit

excavation, which is a complex system with many risks, early and effective prediction of possible outcomes can reduce detrimental effect of incidents and accidents. Available risk prediction methods can be grouped into three—1) empirical, 2) numerical and 3) machine learning.

Empirical approaches are qualitative in nature, which limits their application to a certain construction techniques and ground conditions [91]. It is used for predicting settlement and ground loss [92] [93]. Because of the possibilities to simulate excavation sequences numerically, numerical simulation methods are being implemented to analyze safety and cost constraints, incorporating spatial soil variability and pore pressure measurement [94] [95] [96]. However, recently, machine learning methods have been widely applied in risk prediction, and mainly include time series analysis—TSA [97] [98], Bayesian network—BN [99] [100], support vector machine—SVM [101] [102], artificial neural networks—ANN [103] [104], and random forest—RF [105] [106] [107]. Due to algorithmically and computational simplicity than other methods, applicability of supervised learning method, RF, in deep foundation pits has been validated using monitored data [108]. Owing to the complexity of excavation of foundation pits, there is uncertainty in the monitoring data collected from different types and different monitoring points of the same type. Processing of these data implicitly takes uncertainties into account. In view of this, it is prudent to provide relevant practical insights on the ways of handling the reality of “site-challenges” as a result of evolution of uncertainties from different sources, as presented in Sections 3.

3. Dealing with Uncertainties and Reliability

Geotechnical engineering practice and research are characterized by the uncertainty of time and space, and often encounter many sources of risk or hazards. As shown in **Figure 1**, uncertainties arise from geotechnical inherent uncertainty (measurement error) and/or transformation uncertainty [109]. Transformation uncertainty appears while using empirical or other correlation models and interactions between the ground and structures, both during and after construction [110] [111]. Consequently, it becomes convenient to acquire reliability index or failure probability for specific circumstances in excavation projects, so




Figure 1. Overview of geotechnical uncertainties [109].

that decisions can be made on the relative contribution of sources of uncertainty [112] [113] [114] [115]. Based on the identified and quantified uncertainties, probability factors are developed to define probability of unacceptable performance, which is very important to identify the leading risk category of concern, especially in the design-build (DB) procurement process [116] [117].

Probabilistic considerations in deep foundation have emerged in applications towards excessive differential settlement; analysis of excavation-induced retaining wall deflection, ground movements, and damage potential to an adjacent building with focus on component reliability assessment of serviceability criterion [27] [118] [119] [120]. Occurrence probabilities of risk events, assessment of consequences, and planning of control strategies require to acknowledge the risk at the very end and provide remedial measures to avoid the risk or recovery methods in the event based on informed decisions [121] [122].

Fenton [123], Fenton *et al.* [114], Fenton and Naghibi [124] have made comparison among existing codes regarding periodic updates and revisions for professional practice harmonization. They indicated that countries have already been shifting the national geotechnical design codes of standards towards reliability-based design concepts where separate “partial” factor of safety is employed unlike that of comprehensive one in the traditional method. In this regard, it is prudent to carefully examine what existing (monitoring) data have to implicate in decision making; especially as data is increasingly being considered as “new oil” to the point whereby data is used to support sensitive decisions apart from project compliance purposes [125] [126]. For instance, if one excavation failure phenomenon among the 15 failure categories seen in china [127] is suspected to possibly occur, then the reliability of the critical event can be checked along with observations made as excavation progresses and remedial measures can be deployed to control it early from happening. Therefore, it is not a trivial thing in deep excavation projects to incorporate new knowledge of site conditions as construction progresses in order to make adjustments on the system performance. Within the framework of observational method, real-time observed data are employed timely to act against uncertainties during construction. This requires understanding of the observational method and appropriate real-time data acquisition system.

3.1. Application of Observational Method (OM)

After Peck [128] formally introduced Terzaghi’s “Learn-As-You-Go method”, OM has been successfully applied in practice by progressively modifying the design to minimize potential construction risks over the years [129] [130] [131] [132]. If there is enough time to fully implement the revision plan proposed from ab initio or ipso tempore, the overall economy within the safety margin of the project can be achieved. However, some reticence still remains to its wider use [133] [134]. The reluctance of engineers to change design decisions already made has been now ameliorated through monitored-decision process [135]

[136]. Finno [137] used monitoring data to update performance predictions of supported excavations. Young and Ho [138] and Ikuta *et al.* [139] applied OM in design of supported excavation in which excavation sequence is taken into account to revise and confirm initial design assumptions. Corner effects and time-dependent movements in excavation projects have been dealt within OM framework in the context of EUROCODE 7 by Fuentes, Pillai, and Ferreira [140]. Wu, Ching, and Ou [141] adopted probabilistic OM to “update” wall displacements at later stages from earlier stages of excavation, and proposed “stage correlation” based on database of 22 excavation case histories in Taipei.

Implementing OM limits the risk of damage to a satisfactorily low level. Finno and Calvello [142] developed and tested inverse modelling in updating design predictions using inclinometer data obtained from a 12.2 m deep excavation through soft clays in Chicago. Calvello [143] forwarded an approach combining OM and inverse analysis techniques for continuous model recalibration of geotechnical boundary value problem, as shown in **Figure 2**. This time-dependent iterative model calibration using updated new field observations is termed as “observational modelling”; and is found to be effective in predicting associated soil displacements, provided that model uncertainties are dealt with an adequate engineering judgment. Acquiring a high level of good and sound engineering judgment by observing actual performance while the construction proceeds need an ongoing learning and previous experience [144] [145]. Moreover, much computational benefit is gained from computers. [143]

3.2. Construction Monitoring and Early Warning

As deep excavation pit construction sites generally involve multiple resources in dynamic work task and neighboring structures, the risk warning value needs to be cautiously monitored from the perspective of safety and stability. If the field monitoring result of design performances (be it compression force in the struts




Figure 2. Schematics of: (a) observational method; (b) “observational modelling” approach for updating the design predictions of geotechnical boundary value problems [143].

through strain gauges or load cells; deflection of the wall obtained with inclinometers; ground surface movements via optical surveys, inclinometers and extensometers; and porewater pressures through piezometers) are surpassed, the monitoring personnel sends the forewarning document to overseeing unit to trigger threshold safety alarms [25] [146] [147] [148]. Due to the installation of the instrument, the measurement cost by manual monitoring approach is very high, but emerging safety technology is basically replacing them by the automatic monitoring method. Automatic monitoring mainly works on electromagnetic effects and capacitive effects of sensors [72] [149].

Monitoring performance plays an important role in the construction process. Liu, Ren, and Liu [150] discussed how monitoring-based risk management can be used in risk classification, identification and assessment with early warning in deep excavation engineering. A refined monitoring data can bring good early risk warning. However, as the construction of deep foundation pits continues, the safety risks continue to change, making it difficult to achieve real-time monitoring through traditional safety risk early warning systems [78] [151]. In order to eliminate this drawback, the so called “Building Information Modelling (BIM)” has recently become an inevitable choice owing to its convenience in multi-dimensional visualization and user friendliness [79] [152] [153]. With the advantage to incorporate a time factor in using BIM, an effective safety risk identification and occupational health can be achieved [77] [154] [155]. Qian and Lin [77] also detailed the progress of Chinese real-time online safety risk management.

A safety barrier early warning system using the Internet of Things (IoT) has been implemented in underground construction sites to improve safety management by gathering monitoring data of workers and “things” [71] [148]. The system uses a hazard control alternative, in which the sensing unit, wearable device and monitoring apparatus interact with each other to reduce the contact between hazard energy (danger/risk source) and target (workers, the environment, or physical assets); and recovery enforcement necessary to step away from any potential hazards. An increasing research interest on sensors is putting Information technology (IT)-based construction management into practice [156] [157] [158] [159]. IT-based construction management addresses the following aspects: 1) fast and accurate tracking of construction resources, 2) assuring effectiveness of proximity detection and alerting technology, 3) efforts to replace human operations with robots, and 4) combination of BIM and GIS technologies; in addition, it improves the accuracy and processing time of data, forecasting capability and information feedback.

4. Risk Control Measures

Construction safety risks can be addressed by identifying the consequences of critical risk factors (causes) and evaluating their occurrence probability to select preventive and protective strategies [160] [161]. The notable construction risk

factors according to Tinghua, Siping, and Jingru [160] include design and construction scheme; edge protection; side-wall supporting; drainage measure; loads close to pit side; up-down passage; earth excavation; deformation monitoring; and working environment. These factors contributed to main risk events such as pit collapse, collapse of pit bracing structure, high-fall accident and other causalities. In order to control these risk events, a detailed process is needed that ensures providing satisfactory safety factor during the design process, combined with an inclusive quality control program and monitoring system applicable to the source of risk during the construction process, and applying appropriate contingency plans that fit-for-purpose [162].

As envisioned by the need for economic foundation system in marginal soils and the growing practice of overlaying high-rise structures on piled rafts, it is now inevitable to find new foundation pit excavations adjacent to them. As previously shown in **Table 1**, the performance of foundation pit excavation work has gained much attention. The focus was mainly concentrated to adjacent structure's settlement and more specifically the challenges to neighboring piled foundations. Many studies have attempted to respond by investigating the response of piles, which involves consideration of pile-soil interactions [62] [163] [164]. The ultimate lateral resistance of a pile in a group under passive loading is affected by the pile-soil interaction [165]. Likewise, assessment has to be done for the stability and integrity of piled rafts under the influence of adjacent deep foundation pit excavations. However, when it comes to disconnected piled rafts, the soil-structure interaction mechanism gets even more complex due to the coordinating effect among the raft, cushion, pile and ground. Partly because of this complexity, straightforward solution has not yet been issued and its associated risk has been given little attention. For such a project with intricate boundary conditions, investigating the response of existing foundation would essentially require knowing its current condition and implementing observational method with proper data-interpretation methodology. Due to this distinctive sophistication, an independent peer review (4-eye-principle) on technical matters made by independent experts is highly sought [166] [167].

Compared with research concentration on understanding the load sharing mechanism of disconnected piled rafts [8] [168] [169] [170] [171] [172] and on excavations either on infinite soil or adjacent pile foundations (**Table 1**), little is done on understanding the influence of excavation on nearby piled raft foundations with interposed layer. Zhu *et al.* [173] experimentally evaluated the horizontal bearing characteristics of disconnected piled rafts. They found that the frictional resistance at the interface of mat and cushion layer provides the horizontal resistance to the applied lateral load. However, their load was not passively applied on the piles. Azizkandi *et al.* [174] and Sharma *et al.* [14], for example, have discussed the efficiency of unconnected piled rafts under seismic loading. Recently, focus is placed on the behavior of pile-soil system under lateral soil spreading due to liquefaction [165]. Nevertheless, liquefaction-induced

flow imparts negligible load on the pile due to sudden loss of soil stiffness, which is not experienced by the pile-soil system subjected to excavation induced soil displacement [175] [176].

Wang and Yang [177] performed experimental study on the interaction of new excavation with adjacent high-rise building founded on CFG piled raft. The results of their model test indicated that as the adjacent excavation work was proceeded, the adjustment of the load shared by the CFG piles continued in a complex manner of joint interaction among the pit retaining structure (piles), composite ground and strip of soil column between pit supporting piles and CFG pile composite ground. The centrifuge experimental test performed by Li, Huang, and Han [178] also confirmed the same and revealed the presence of CFG piles reduces the active earth pressure compared to the conventional Rankine theory. Yan-qing Wei [179] also performed indoor model test. The results showed that as the retaining wall was moved, the sliding surface in the retained soil was different from the conventional slip surface because of the piles (see **Figure 3**). Furthermore, the same study pointed out that that with the gradual movement of the wall, the load transmitted to the piles' head increased and consequently, the load shared by the soil decreased, see **Figure 4**. The numerical analysis of Ren and Qiao [180] showed that with an increase in excavation depth, the lateral displacement of the CFG piles increases.

On the other hand, according to some research results, because the axial working load has little effect on the lateral response of pile, once the serviceability limit is exceeded, it may cause sudden damage and collapse of the pile without any signal [64] [181]. Moving on, the lateral response behavior of front piles is highly affected by excavation induced extra passive loading than the rear ones [66] [182] [183]. Therefore, it may be necessary to check whether the structural and geotechnical capacity of the pile is sufficient to withstand the passive load applied due to ground movement caused by excavation. In order to eliminate such and other risks (see **Table 2**), engineering experience and judgment play a significant role. In the risk management process, engineering experience and






Figure 3. Potential failure surface in the soil behind a retaining wall under (a) rotation about its base; (b) translational mode [179].

Table 2. Selected potential risks with countermeasure suggestion and/or comments.

Objective	Target	Risk/event source	Methodology	Remedies/comment
Deep excavation assuring protected environment	1) Controlling foundation pit deformation; 2) Limiting ground movement (sudden ground loss or subsidence)		Spatial geo-material variation & uncertainties (different site conditions)	Inverse analysis based on observations during excavation to confirm actual & design assumption; Enhance soil strength by grouting; Turn to appropriate construction method to suit unanticipated condition
			Leakage & hydraulic failures	End-plate method connection for diaphragm wall joints; With relief wells release confined aquifer pressure; Waterproof curtain by mixed-in-place technology; Prevent uplifting by hybrid of jet grouting & deep soil mixing
			Geotechnical conditions	Zoned construction method (quick excavation, prompt propping, casting rigid floor slab timely); Provide sufficient wall embedment & adequate passive resistance (including stiffness of retaining wall-strut system, soil/anchor length with soil voids filled by grout); Increase unloading moduli of basal stratum with ground improvements
			Global and/or localized soil and excavation support structure failure	Consider optimum compromise to account for path- and state-dependent soil properties; Insufficient level of detailing and design accuracy
			Selection of proper constitutive model (model simplification and omissions)	Construction of isolation/barrier piles to reduce imposed external passive loading (bending moment and forces) on piles
			Structural and geotechnical failure of existing piles	Avoid over-excavation to prevent toppling; Compensation grouting
			Abrupt loss of foundation bearing capacity	Component and system fragility assessment for limiting tensile strain (reliability analysis approach)
			Tensile strains induced in a building	Renovation, backfilling and underpinning to limit distortions in the sagging and hogging zones
			Differential foundation settlement; movement and rotation at pile head	Risk transfer through negotiated exception clauses included in the bid or through claims
			Uncertainties in performance measurements as required by the contract	The traditional design-bid-build is ineffective in minimizing adversarial relationships
	Amount of risk willingly taken by the owner	Continues performance & productivity monitoring with 4-eye principle; Turn to Design-Build or Construction-Management at work mode of project delivery		
	Project-delivery system	Poor on-site management & communication	Change of related-low and regulations; Price escalations, payment delays, etc.	
		Political and financial related		



(a)



(b)

Figure 4. Influence of retaining wall movement on the average stress of soil between piles and pile head of composite foundation under a working vertical load of 88 kPa (a) rotation about the base; and (b) under translation mode [179].

judgment will normalize the decisions regarding Contractor's means and methods, choosing appropriate and mature technology, and dealing with uncertainties in design and construction phases [116] [184] [185] [186].

5. Risk Management Process

It is not enough to understand the probability and consequences of each risk event. There is a need for a systematic method called a risk management process that responds to minimize adverse risk by transferring, avoiding, mitigating or accepting specific risk elements among risk owners and action parties, as illustrated in **Figure 5** [76] [87] [187] [188] [189]. There is also a need for a system that delivers information appropriately at the right time to ensure that the identified risks and their treatment plans are well communicated [188]. For example,




Figure 5. Risk management process for construction projects [187] [188] [189].

the case studies of 50 Dutch underground deep excavation projects in the Netherlands conducted by M. Korff [82] indicated that evaluating and documenting risks during the project by itself is not sufficient to prevent failures but also the lesson systematically gained for the next stage or project needs to be incorporated. In the same report, it was shown that the knowledge to prevent 60% failures existed outside the project, indicating clearly that it is not common to learn regularly between projects. O'Neil [190] also argues to involve all project personnel to search for opportunities in order to enhance margins with constant anticipation and conscientious efficiency in all areas. Similarly, the study on safety risk management for Chinese large scale subway and underground construction projects pointed out that weak risk management mechanism is the leading cause of economic losses and casualties [191].

In general, the approach for risk management and response strategy can either be applied through risk control (by avoiding, loss reduction, risk prevention, and risk transfer) or financing the losses that may occur [189]. While applying observational modelling, the lesson learnt from the earlier stage of the same project is used to reduce the size of the initial risk. Progressive application of such dynamic risk management is termed as Multiphase Risk Management Method [192] [193]. Furthermore, the cushion layer compressibility and the interaction effects among each pile while the soil moves around the piles would require 3D finite element analysis. It is worth noting that when implementing risk response strategies, back analysis with pit and ground deformation control criteria as well as monitoring based risk tracking by considering risk interdependences play an important role. Needless to say, achieving project objectives and successful deli-

very largely depends on how the risk management and response strategy is practically structured and properly implemented among concerned parties.

6. Future Research

Despite project managers are fully cognizant and give much attention to high-risk projects, the following issues are worthy of further study:

- Holistic geotechnical risk management plan from the perspective of stakeholders. Often statistical results were reported on previous studies, thus, further study is suggested on the risk diagnostics to refine the bias sources and risk decision theory.
- Issues related to risk and knowledge management at the company and site level. Is there any structured knowledge sharing platform to capture, encode and transfer lessons gained from organization's practice and experience in deep foundation pit excavation?
- More parametric numerical studies on the load transfer mechanism and excavation-induced settlement characteristics. Since disconnecting the pile from the raft is a novel practice, more and more researches are needed to fully understand the complex soil-structure interaction due to the presence of the deformable cushion layer.
- Advanced technologies to capture the soil-structure interaction experimentally. In fact, the current experimental setup lags behind perfection to take into consideration factors such as superstructure stiffness, retaining wall installation, and embedded basement slabs (mats).
- Back analysis during OM highly depends on the model parameters. Thus, further study may be necessary to understand the non-linear soil stress-strain response under different loading/loading states due to excavation.

7. Conclusions

This paper dissects the risk management approach from the perspective of geotechnical engineering and enlightens the need to account for risk interdependences and proper communication of lesson learned from other projects and/or ongoing ones. To this aim, based on risk triggering conditions, risk/event sources can be categorized broadly into 1) geotechnical conditions, 2) surrounding environment, and 3) project delivery system. For deep foundation pit excavations in congested urban dwellings, the risk control practice is essentially concentrated on limiting foundation pit deformation and associated ground displacements to an allowable amount that ensures serviceability limit state requirements are met.

Supplemented with sound engineering judgment, a well-posed observational modelling allows to better understand the load and deformation behaviors of the foundation pit and adjacent on-service foundations. If the expected performance cannot be achieved during the observation period, rigorous and timely research on the uncertain parameters and predicting their potential impact will provide reliable elements for risk-based decision-making. Currently, numerical simula-

tions are widely used to assess the effect of ground movement on piles.

Each deep foundation pit excavation has its own challenges to take lessons from it due to the very nature of pertinence and strong locality. Although it is not necessarily copied and pasted, the essential information systematically explored out of the “dark data” of the completed project and/or the ongoing monitoring data can avoid failures. Therefore, proper communication of such information is germane to the competency of decision makers along the risk management process. It eliminates predictable risk events. Yet, comprehensive future study is needed to fully understand the behavior of disconnected piled rafts subjected to excavation-induced soil movements.

Acknowledgements

The authors gratefully acknowledge the support of Zhengzhou University’s Presidential Scholarship Program for sponsoring the research area “Foundation Treatment and Foundation Pit Support Engineering”.

Conflicts of Interest

The authors declare no conflicts of interest regarding the publication of this paper.

References

- [1] Poulos, H.G. (2016) Tall Building Foundations: Design Methods and Applications. *Innovative Infrastructure Solutions*, **1**, Article No. 10. <https://doi.org/10.1007/s41062-016-0010-2>
- [2] Han, J. (2015) Recent Research and Development of Ground Column Technologies. *Proceedings of the Institution of Civil Engineers—Ground Improvement*, **168**, 246-264. <https://doi.org/10.1680/grim.13.00016>
- [3] Niu, X., Yao, Y., Sun, Y., *et al.* (2018) 3D Numerical Analysis of Synergetic Interaction between High-Rise Building Basement and CFG Piles Foundation. *Applied Sciences*, **8**, 2040. <https://doi.org/10.3390/app8112040>
- [4] Yuan, Y., Liu, A., Jiao, Y. and Liu, C. (2018) Field Detection and Simulation Analysis of CFG Pile Composite Foundation. *Hans Journal of Civil Engineering*, **7**, 906-918. <https://doi.org/10.12677/HJCE.2018.76109>
- [5] Zhang, Y.T., Tao, L.J., Tang, S.H. and Sun, B. (2008) Research on the Proper Selection of Soil Constitutive Relation in Modeling Underground Excavation. *Materials Science Forum*, **575-578**, 1358-1363. <https://doi.org/10.4028/www.scientific.net/MSF.575-578.1358>
- [6] Rui, R., Han, J., Ye, Y., *et al.* (2020) Load Transfer Mechanisms of Granular Cushion between Column Foundation and Rigid Raft. *International Journal of Geomechanics*, **20**, Article ID: 04019139. [https://doi.org/10.1061/\(ASCE\)GM.1943-5622.0001539](https://doi.org/10.1061/(ASCE)GM.1943-5622.0001539)
- [7] Baziar, M.H., Rafiee, F., Lee, C.J. and Azizkandi, A.S. (2018) Effect of Superstructure on the Dynamic Response of Nonconnected Piled Raft Foundation Using Centrifuge Modeling. *International Journal of Geomechanics*, **18**, Article ID: 04018126. [https://doi.org/10.1061/\(ASCE\)GM.1943-5622.0001263](https://doi.org/10.1061/(ASCE)GM.1943-5622.0001263)

- [8] Wong, I.H., Chang, M.F., Cao, X.D. and Hemsley, J.A. (2000) Raft Foundations with Disconnected Settlement-Reducing Piles. In: Hemsley, J.A., Ed., *Design Applications of Raft Foundations*, Thomas Telford Publishing, London, 469-486. <https://doi.org/10.1680/daorf.27657.0017>
- [9] Fioravante, V. (2011) Load Transfer from a Raft to a Pile with an Interposed Layer. *Geotechnique*, **61**, 121-132. <https://doi.org/10.1680/geot.7.00187>
- [10] Azizkandi, A.S., Rasouli, H. and Baziar, M.H. (2019) Load Sharing and Carrying Mechanism of Piles in Non-Connected Pile Rafts Using a Numerical Approach. *International Journal of Civil Engineering*, **17**, 793-808. <https://doi.org/10.1007/s40999-018-0356-2>
- [11] Cao, X.D., Wong, I.H. and Chang, M.-F. (2004) Behavior of Model Rafts Resting on Pile-Reinforced Sand. *Journal of Geotechnical and Geoenvironmental Engineering*, **130**, 129-138. [https://doi.org/10.1061/\(ASCE\)1090-0241\(2004\)130:2\(129\)](https://doi.org/10.1061/(ASCE)1090-0241(2004)130:2(129))
- [12] Al-Abboodi, I. and Sabbagh, T.T. (2018) Model Tests on Piled Raft Subjected to Lateral Soil Movement. *International Journal of Geotechnical Engineering*, **12**, 357-367. <https://doi.org/10.1080/19386362.2017.1296061>
- [13] Rasouli, H., Azizkandi, A.S., Baziar, M.H., *et al.* (2015) Centrifuge Modeling of Non-Connected Piled Raft System. *International Journal of Civil Engineering*, **13**, 114-123.
- [14] Sharma, V.J., Vasanvala, S.A. and Solanki, C.H. (2015) Study of Cushioned Composite Piled Raft Foundation Behaviour under Seismic Forces. *Australian Journal of Civil Engineering*, **13**, 32-39. <https://doi.org/10.1080/14488353.2015.1092636>
- [15] Tradigo, F., Pisanò, F., Di Prisco, C. and Mussi, A. (2015) Non-Linear Soil-Structure Interaction in Disconnected Piled Raft Foundations. *Computers and Geotechnics*, **63**, 121-134. <https://doi.org/10.1016/j.compgeo.2014.08.014>
- [16] Basu, D., Misra, A. and Puppala, A.J. (2015) Sustainability and Geotechnical Engineering: Perspectives and Review. *Canadian Geotechnical Journal*, **52**, 96-113. <https://doi.org/10.1139/cgj-2013-0120>
- [17] Hunt, D.V.L., Makana, L.O., Jefferson, I. and Rogers, C.D.F. (2016) Liveable Cities and Urban Underground Space. *Tunnelling and Underground Space Technology*, **55**, 8-20. <https://doi.org/10.1016/j.tust.2015.11.015>
- [18] Magsino, S.L., Gilbert, P.H., Ariaratnam, S.T., *et al.* (2014) Underground Engineering for Sustainable Urban Development. *Geo-Congress 2014 Technical Papers*, American Society of Civil Engineers, Atlanta, 23-26 February 2014, 3861-3870. <https://doi.org/10.1061/9780784413272.374>
- [19] Ai L (2016) The Research on Support and Reinforcement of Deep Foundation Pit. *Proceedings of the 2016 4th International Conference on Management, Education, Information and Control (MEICI 2016)*, Shenyang, 24-26 September 2016, 661-665. <https://doi.org/10.2991/meici-16.2016.138>
- [20] Ou, C.-Y. (2006) *Deep Excavation: Theory and Practice*. Taylor & Francis, London.
- [21] Kishii, T. (2016) Utilization of Underground Space in Japan. *Tunnelling and Underground Space Technology*, **55**, 320-323. <https://doi.org/10.1016/j.tust.2015.12.007>
- [22] Popa, H., Manea, S., Batali, L. and Olteanu, A. (2013) Aspects on Designing and Monitoring a Deep Excavation for a Highly Important Structure. *Proceedings of the 18th International Conference on Soil Mechanics and Geotechnical Engineering*, Paris, 2-6 September 2013, 2079-2082.
- [23] Katzenbach, R. and Bachmann, G. (2007) Continuous Monitoring of Deep Excava-

- tion Pits for Damage Prevention. *7th International Symposium on Field Measurements in Geomechanics*, Boston, 24-27 September 2007, 1-12.
[https://doi.org/10.1061/40940\(307\)28](https://doi.org/10.1061/40940(307)28)
- [24] Tye, T.A. and Marr, W.A. (2011) Risk Management with Performance-Based Geoenvironmental Monitoring: APM Tunnel Extension at Hartsfield-Jackson International Airport. *Proceedings of GeoRisk 2011: Geotechnical Risk Assessment and Management*, 26-28 June 2011, Atlanta, 26-28 June 2011, 971-978.
[https://doi.org/10.1061/41183\(418\)105](https://doi.org/10.1061/41183(418)105)
- [25] Wang, H., Yang, H., Dong, X. and Ni, S. (2010) Safety Monitoring and Early Warning for Deep Foundation Pit Construction. *10th International Conference of Chinese Transportation Professionals*, Beijing, 4-8 August 2010, 3493-3500.
[https://doi.org/10.1061/41127\(382\)377](https://doi.org/10.1061/41127(382)377)
- [26] Puzrin, A.M., Alonso, E.E. and Pinyol, N.M. (2010) Braced Excavation Collapse: Nicoll Highway, Singapore. In: *Geomechanics of Failures*, Springer, Dordrecht, 151-181. https://doi.org/10.1007/978-90-481-3531-8_6
- [27] Zhou, H. and Zhang, H. (2011) Risk Assessment Methodology for a Deep Foundation Pit Construction Project in Shanghai, China. *Journal of Construction Engineering and Management*, **137**, 1185-1194.
[https://doi.org/10.1061/\(ASCE\)CO.1943-7862.0000391](https://doi.org/10.1061/(ASCE)CO.1943-7862.0000391)
- [28] Chai, J., Shen, S., Ding, W., *et al.* (2014) Numerical Investigation of the Failure of a Building in Shanghai, China. *Computers and Geotechnics*, **55**, 482-493.
<https://doi.org/10.1016/j.compgeo.2013.10.001>
- [29] Rowson, J. (2009) Cologne: Groundwater Extraction Method Probed. *New Civil Engineer*.
<http://www.nce.co.uk/print-magazine/cologne-groundwater-extraction-method-probed/1995535.article>
- [30] Bilgin, Ö., Mansour, E. and Gabar, M. (2011) Serviceability Considerations in the Design of Sheet Pile Walls for Risk Management. *Proceedings of GeoRisk 2011: Geotechnical Risk Assessment and Management*, 26-28 June 2011, Atlanta, Georgia, 26-28 June 2011, 754-761. [https://doi.org/10.1061/41183\(418\)78](https://doi.org/10.1061/41183(418)78)
- [31] Jurečić, N., Zdravković, L. and Jovičić, V (2013) Predicting Ground Movements in London Clay. *Proceedings of the Institution of Civil Engineers—Geotechnical Engineering*, **166**, 466-482. <https://doi.org/10.1680/geng.11.00079>
- [32] Mu, L. and Huang, M. (2016) Small Strain Based Method for Predicting Three-Dimensional Soil Displacements Induced by Braced Excavation. *Tunnelling and Underground Space Technology*, **52**, 12-22.
<https://doi.org/10.1016/j.tust.2015.11.001>
- [33] Chen, H., Li, J., Yang, C. and Feng, C. (2020) A Theoretical Study on Ground Surface Settlement Induced by a Braced Deep Excavation. *European Journal of Environmental and Civil Engineering*, 1-20.
<https://doi.org/10.1080/19648189.2020.1739563>
- [34] Sekhavatia, A. and Janalizade, A. (2018) Comparison of Constitutive Soil Models in Predicting Movements Caused by an Underground Excavation. *International Journal of Soil Science*, **13**, 18-27. <https://doi.org/10.3923/ijss.2018.18.27>
- [35] Wang, L.Z., Liu, Y.J., Hong, Y. and Liu, S.M. (2018) Predicting Deformation of Multipropped Excavations in Soft Clay with a Modified Mobilizable Strength Design (MMSD). Method. *Computers and Geotechnics*, **104**, 54-68.
<https://doi.org/10.1016/j.compgeo.2018.07.018>

- [36] Finno, R.J., Kim, S., Lewis, J. and Van Winkle, N. (2019) Observed Performance of A Sheetpile-Supported Excavation in Chicago Clays. *Journal of Geotechnical and Geoenvironmental Engineering*, **145**, Article ID: 05018005. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0002010](https://doi.org/10.1061/(ASCE)GT.1943-5606.0002010)
- [37] Li, S., Huang, Z., Zhao, K., *et al.* (2019) Comparative Analysis of Pit Deformation Characteristics in Typical Region Soft Soil Deposits of China. *Arabian Journal of Geosciences*, **12**, Article No. 376. <https://doi.org/10.1007/s12517-019-4534-6>
- [38] Yang, X., Jia, M. and Ye, J. (2020) Method for Estimating Wall Deflection of Narrow Excavations in Clay. *Computers and Geotechnics*, **117**, Article ID: 103224. <https://doi.org/10.1016/j.compgeo.2019.103224>
- [39] Pujades, E., Vázquez-Suñé, E., Carrera, J. and Jurado, A. (2014) Dewatering of a Deep Excavation Undertaken in a Layered Soil. *Engineering Geology*, **178**, 15-27. <https://doi.org/10.1016/j.enggeo.2014.06.007>
- [40] Xu, Y.-S., Wu, H.-N., Wang, B.Z.-F. and Yang, T.-L. (2017) Dewatering Induced Subsidence during Excavation in a Shanghai Soft Deposit. *Environmental Earth Sciences*, **76**, Article No. 351. <https://doi.org/10.1007/s12665-017-6685-7>
- [41] Zhang, W.G., Goh, A.T.C., Goh, K.H., *et al.* (2018) Performance of Braced Excavation in Residual Soil with Groundwater Drawdown. *Underground Space*, **3**, 150-165. <https://doi.org/10.1016/j.undsp.2018.03.002>
- [42] Wu, Y.-X., Lyu, H.-M., Han, J. and Shen, S.-L. (2019) Dewatering-Induced Building Settlement around a Deep Excavation in Soft Deposit in Tianjin, China. *Journal of Geotechnical and Geoenvironmental Engineering*, **145**, Article ID: 05019003. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0002045](https://doi.org/10.1061/(ASCE)GT.1943-5606.0002045)
- [43] Cheng, W.-C., Li, G., Liu, N., *et al.* (2020) Recent Massive Incidents for Subway Construction in Soft Alluvial Deposits of Taiwan: A Review. *Tunnelling and Underground Space Technology*, **96**, Article ID: 103178. <https://doi.org/10.1016/j.tust.2019.103178>
- [44] Juang, C.H., Wang, L., Hsieh, H.-S. and Atamturktur, S. (2014) Robust Geotechnical Design of Braced Excavations in Clays. *Structural Safety*, **49**, 37-44. <https://doi.org/10.1016/j.strusafe.2013.05.003>
- [45] Wang, L., Juang, C.H., Atamturktur, S., *et al.* (2014) Optimization of Design of Supported Excavations in Multi-Layer Strata. *Journal of GeoEngineering*, **9**, 1-12.
- [46] Liu, B. and Sun, F. (2015) Study on the Optimization System of Supporting Schemes for Foundation Pit. *Vibroengineering Procedia*, **5**, 429-435.
- [47] Guo, Y. and Zhou, T. (2016) Numerical Analysis and Engineering Application of New Composite Support System. Science Press, Beijing.
- [48] Tan, Y.-C., Chow, C.-M., Koo, K.-S. and Nazir, R. (2016) Challenges in Design and Construction of Deep Excavation for KVMRT in Kuala Lumpur Limestone formation. *Jurnal Teknologi*, **78**, 97-107.
- [49] Alipour, A. and Eslami, A. (2019) Design Adaptations in a Large and Deep Urban Excavation: Case Study. *Journal of Rock Mechanics and Geotechnical Engineering*, **11**, 389-399. <https://doi.org/10.1016/j.jrmge.2018.08.014>
- [50] Yang, J., Chen, J., Xie, Z., *et al.* (2014) Study on the Control of Surrounding Environment Deformation by the Pit-Divided Method. *Geo-Shanghai 2014*, Shanghai, 26-28 May 2014, 363-375. <https://doi.org/10.1061/9780784413449.036>
- [51] Li, M.-G., Zhang, Z.-J., Chen, J.-J., *et al.* (2017) Zoned and Staged Construction of an Underground Complex in Shanghai Soft Clay. *Tunnelling and Underground Space Technology*, **67**, 187-200. <https://doi.org/10.1016/j.tust.2017.04.016>

- [52] Li, M.-G., Chen, J.-J., Xu, A.-J., *et al.* (2014) Case Study of Innovative Top-Down Construction Method with Channel-Type Excavation. *Journal of Construction Engineering and Management*, **140**, Article ID: 05014003. [https://doi.org/10.1061/\(ASCE\)CO.1943-7862.0000828](https://doi.org/10.1061/(ASCE)CO.1943-7862.0000828)
- [53] Chen, J.-J., Zhu, Y.-F., Li, M.-G. and Wen, S.-L. (2015) Novel Excavation and Construction Method of an Underground Highway Tunnel above Operating Metro Tunnels. *Journal of Aerospace Engineering*, **28**, Article ID A4014003. [https://doi.org/10.1061/\(ASCE\)AS.1943-5525.0000437](https://doi.org/10.1061/(ASCE)AS.1943-5525.0000437)
- [54] Tan, Y., Wei, B., Zhou, X. and Diao, Y. (2015) Lessons Learned from Construction of Shanghai Metro Stations: Importance of Quick Excavation, Prompt Propping, Timely Casting, and Segmented Construction. *Journal of Performance of Constructed Facilities*, **29**, Article ID: 04014096. [https://doi.org/10.1061/\(ASCE\)CF.1943-5509.0000599](https://doi.org/10.1061/(ASCE)CF.1943-5509.0000599)
- [55] Rotisciani, G.M., Miliziano, S. and Sacconi, S. (2016) Design, Construction, and Monitoring of a Building with Deep Basements in Rome. *Canadian Geotechnical Journal*, **53**, 210-224. <https://doi.org/10.1139/cgj-2015-0244>
- [56] Zhang, Z.-J., Li, M.-G., Chen, J.-J., *et al.* (2017) Innovative Construction Method for Oversized Excavations with Bipartition Walls. *Journal of Construction Engineering and Management*, **143**, Article ID: 04017056. [https://doi.org/10.1061/\(ASCE\)CO.1943-7862.0001357](https://doi.org/10.1061/(ASCE)CO.1943-7862.0001357)
- [57] Chen, H., Li, J. and Li, L. (2018) Performance of a Zoned Excavation by Bottom-Up Technique in Shanghai Soft Soils. *Journal of Geotechnical and Geoenvironmental Engineering*, **144**, Article ID: 05018003. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0001964](https://doi.org/10.1061/(ASCE)GT.1943-5606.0001964)
- [58] Tan, Y., Lu, Y. and Wang, D. (2019) Practical Solutions for Concurrent Excavation of Neighboring Mega Basements Closely Surrounded by Utility Tunnels in Shanghai Hongqiao CBD. *Practice Periodical on Structural Design and Construction*, **24**, Article ID: 05019005. [https://doi.org/10.1061/\(ASCE\)SC.1943-5576.0000437](https://doi.org/10.1061/(ASCE)SC.1943-5576.0000437)
- [59] Fantaziu, C. and Chirilă, R. (2014) Study Achievement of Deep Excavations from the Point of View of Their Effects on Surrounding Existing Buildings. *Journal of Sustainable Architecture and Civil Engineering*, **7**, 74-80. <https://doi.org/10.5755/j01.sace.7.2.6857>
- [60] Goh, K.H. and Mair, R.J. (2014) Response of Framed Buildings to Excavation-Induced Movements. *Soils and Foundations*, **54**, 250-268. <https://doi.org/10.1016/j.sandf.2014.04.002>
- [61] Benin, A., Konkov, A., Kavkazskiy, V., *et al.* (2016) Evaluation of Deformations of Foundation Pit Structures and Surrounding Buildings during the Construction of the Second Scene of the State Academic Mariinsky Theatre in Saint-Petersburg Considering Stage-by-Stage Nature of Construction Process. *Procedia Engineering*, **165**, 1483-1489. <https://doi.org/10.1016/j.proeng.2016.11.883>
- [62] Korff, M., Mair, R.J. and Van Tol, F.A.F. (2016) Pile-Soil Interaction and Settlement Effects Induced by Deep Excavations. *Journal of Geotechnical and Geoenvironmental Engineering*, **142**, Article ID: 04016034. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0001434](https://doi.org/10.1061/(ASCE)GT.1943-5606.0001434)
- [63] Liang, R., Xia, T., Huang, M. and Lin, C. (2017) Simplified Analytical Method for Evaluating the Effects of Adjacent Excavation on Shield Tunnel Considering the Shearing Effect. *Computers and Geotechnics*, **81**, 167-187. <https://doi.org/10.1016/j.compgeo.2016.08.017>
- [64] Liyanapathirana, D.S. and Nishanthan, R. (2016) Influence of Deep Excavation In-

- duced Ground Movements on Adjacent Piles. *Tunnelling and Underground Space Technology*, **52**, 168-181. <https://doi.org/10.1016/j.tust.2015.11.019>
- [65] Shakeel, M. and Ng, C.W.W. (2018) Settlement and Load Transfer Mechanism of a Pile Group Adjacent to a Deep Excavation in Soft Clay. *Computers and Geotechnics*, **96**, 55-72. <https://doi.org/10.1016/j.compgeo.2017.10.010>
- [66] Soomro, M.A., Mangnejo, D.A., Bhanbhro, R., *et al.* (2019) 3D Finite Element Analysis of Pile Responses to Adjacent Excavation in Soft Clay: Effects of Different Excavation Depths Systems Relative to a Floating Pile. *Tunnelling and Underground Space Technology*, **86**, 138-155. <https://doi.org/10.1016/j.tust.2019.01.012>
- [67] Cui, K., Feng, J. and Zhu, C. (2018) A Study on the Mechanisms of Interaction between Deep Foundation Pits and the Pile Foundations of Adjacent Skewed Arches as Well as Methods for Deformation Control. *Complexity*, **2018**, Article ID: 6535123.
- [68] Li, D. and Yan, C. (2018) Building Deformation Prediction Based on Ground Surface Settlements of Metro-Station Deep Excavation. *Advances in Civil Engineering*, **2018**, Article ID: 6050353.
- [69] Son, M. and Cording, E.J. (2020) Estimation of Building Damage in a 3D Distorting Structure to Tunnel and Underground Excavation-Induced Ground Movements. *Tunnelling and Underground Space Technology*, **97**, Article ID: 103222. <https://doi.org/10.1016/j.tust.2019.103222>
- [70] Fearnhead, N., Maniscalco, K., Standing, J.R. and Wan, M.S.P. (2014) Deep Excavations: Monitoring Mechanisms of Ground Displacement. *Proceedings of the Institution of Civil Engineers—Geotechnical Engineering*, **167**, 117-129. <https://doi.org/10.1680/geng.13.00047>
- [71] Zhou, C. and Ding, L.Y. (2017) Safety Barrier Warning System for Underground Construction Sites Using Internet-of-Things Technologies. *Automation in Construction*, **83**, 372-389. <https://doi.org/10.1016/j.autcon.2017.07.005>
- [72] Lv, J., Hu, Z., Ren, G., *et al.* (2019) Research on New FBG Displacement Sensor and Its Application in Beijing Daxing Airport Project. *Optik*, **178**, 146-155. <https://doi.org/10.1016/j.ijleo.2018.09.117>
- [73] Moffat, R., Parra, P. and Carrasco, M. (2019) Monitoring a 28.5 m High Anchored Pile Wall in Gravel Using Various Methods. *Sensors*, **20**, 80. <https://doi.org/10.3390/s20010080>
- [74] Zhu, C., Yan, Z., Lin, Y., *et al.* (2019) Design and Application of a Monitoring System for a Deep Railway Foundation Pit Project. *IEEE Access*, **7**, 107591-107601. <https://doi.org/10.1109/ACCESS.2019.2932113>
- [75] Aizhao, Z., Xu, J.P. and Han, X.W. (2010) Research on Protection Technology of Foundation Pit Excavation Adjacent to Existing Railway. 2010 *International Conference on Optoelectronics and Image Processing*, Haiko, 11-12 November 2010, 270-273. <https://doi.org/10.1109/ICOIP.2010.86>
- [76] Nie, S.M. and Liu, J.Y. (2014) The Risk Management Practice of a Deep Foundation Pit Project. *Applied Mechanics and Materials*, **638-640**, 703-709.
- [77] Qian, Q. and Lin, P. (2016) Safety Risk Management of Underground Engineering in China: Progress, Challenges and Strategies. *Journal of Rock Mechanics and Geotechnical Engineering*, **8**, 423-442. <https://doi.org/10.1016/j.jrmge.2016.04.001>
- [78] Zhou, Y., Su, W., Ding, L., *et al.* (2017) Predicting Safety Risks in Deep Foundation Pits in Subway Infrastructure Projects: Support Vector Machine Approach. *Journal of Computing in Civil Engineering*, **31**, Article ID: 04017052.

- [https://doi.org/10.1061/\(ASCE\)CP.1943-5487.0000700](https://doi.org/10.1061/(ASCE)CP.1943-5487.0000700)
- [79] Li, M., Yu, H., Jin, H. and Liu, P. (2018) Methodologies of Safety Risk Control for China's Metro Construction Based on BIM. *Safety Science*, **110**, 418-426. <https://doi.org/10.1016/j.ssci.2018.03.026>
- [80] Han, J., Zhao, W., Jia, P., *et al.* (2018) Risk Analysis of the Opening of Shield-Tunnel Circumferential Joints Induced by Adjacent Deep Excavation. *Journal of Performance of Constructed Facilities*, **32**, Article ID: 04017123. [https://doi.org/10.1061/\(ASCE\)CF.1943-5509.0001122](https://doi.org/10.1061/(ASCE)CF.1943-5509.0001122)
- [81] Zhu, M., Gong, X., Gao, X., *et al.* (2019) Remediation of Damaged Shield Tunnel Using Grouting Technique: Serviceability Improvements and Prevention of Potential Risks. *Journal of Performance of Constructed Facilities*, **33**, Article ID: 04019062. [https://doi.org/10.1061/\(ASCE\)CF.1943-5509.0001335](https://doi.org/10.1061/(ASCE)CF.1943-5509.0001335)
- [82] Korff, M. (2017) Case Studies and Monitoring of Deep Excavations. In: Negro, A. and Cecilio, M.O., Eds., *Geotechnical Aspects of Underground Construction in Soft Ground*, CRC Press, Boca Raton, 23-31. <https://doi.org/10.1201/9781315099507-2>
- [83] Marr, W.A. (2006) Geotechnical Engineering and Judgment in the Information Age. *GeoCongress 2006: Geotechnical Engineering in the Information Technology Age*, Atlanta, 26 February-1 March 2006, 1-17. [https://doi.org/10.1061/40803\(187\)4](https://doi.org/10.1061/40803(187)4)
- [84] Juang, C.H., Gong, W., Martin, J.R. and Chen, Q. (2018) Model Selection in Geological and Geotechnical Engineering in the Face of Uncertainty—Does a Complex Model Always Outperform a Simple Model? *Engineering Geology*, **242**, 184-196. <https://doi.org/10.1016/j.enggeo.2018.05.022>
- [85] Carmichael, D.G. (2020) Bias and Decision Making—An Overview Systems Explanation. *Civil Engineering and Environmental Systems*, **37**, 48-61. <https://doi.org/10.1080/10286608.2020.1744133>
- [86] Elms, D. (2019) Limitations of Risk Approaches. *Civil Engineering and Environmental Systems*, **36**, 2-16. <https://doi.org/10.1080/10286608.2019.1615474>
- [87] Ben-David, I. and Raz, T. (2001) An Integrated Approach for Risk Response Development in Project Planning. *Journal of the Operational Research Society*, **52**, 14-25. <https://doi.org/10.1057/palgrave.jors.2601029>
- [88] Li, N., Fang, D. and Sun, Y. (2016) Cognitive Psychological Approach for Risk Assessment in Construction Projects. *Journal of Management in Engineering*, **32**, Article ID: 04015037. [https://doi.org/10.1061/\(ASCE\)ME.1943-5479.0000397](https://doi.org/10.1061/(ASCE)ME.1943-5479.0000397)
- [89] PMI (Project Management Institute) (2017) A Guide to the Project Management Body of Knowledge/Project Management Institute. 6th Edition, Project Management Institute, Newtown Square.
- [90] Zhang, Y. (2016) Selecting Risk Response Strategies Considering Project Risk Interdependence. *International Journal of Project Management*, **34**, 819-830. <https://doi.org/10.1016/j.ijproman.2016.03.001>
- [91] Loganathan, N. and Poulos, H.G. (1998) Analytical Prediction for Tunneling-Induced Ground Movements in Clays. *Journal of Geotechnical and Geoenvironmental Engineering*, **124**, 846-856. [https://doi.org/10.1061/\(ASCE\)1090-0241\(1998\)124:9\(846\)](https://doi.org/10.1061/(ASCE)1090-0241(1998)124:9(846))
- [92] Burland, J.B., Standing, J.R. and Jardine, F.M. (2001) Building Response to Tunneling, Case Studies from Construction of the Jubilee Line Extension, London. The Results of the Collaborative Research Project Subsidence Damage to Buildings: Prediction, Protection and Repair. Imperial College with the Sponsorship of London Underground Limited, Telford, London.
- [93] Wei, Y., He, J., Pan, H.Z. and Luo, Z.H. (2017) Research on Foundation Pit Con-

- struction Risk of Metro Station Based on Fuzzy Entropy Theory. *DEStech Transactions on Engineering and Technology Research*, 173-180.
<https://doi.org/10.12783/dtetr/mcae2017/15959>
- [94] Whittle, A.J., Hashash, Y.M.A. and Whitman, R.V. (1993) Analysis of Deep Excavation in Boston. *Journal of Geotechnical Engineering*, **119**, 69-90.
[https://doi.org/10.1061/\(ASCE\)0733-9410\(1993\)119:1\(69\)](https://doi.org/10.1061/(ASCE)0733-9410(1993)119:1(69))
- [95] Whittle, A.J., Corral, G., Jen, L.C. and Rawnsley, R.P. (2015) Prediction and Performance of Deep Excavations for Courthouse Station, Boston. *Journal of Geotechnical and Geoenvironmental Engineering*, **141**, Article ID: 04014123.
[https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0001246](https://doi.org/10.1061/(ASCE)GT.1943-5606.0001246)
- [96] Zhang, L., Wu, X., Chen, Q., *et al.* (2014) Towards a Safety Management Approach for Adjacent Buildings in Tunneling Environments: Case Study in China. *Building and Environment*, **75**, 222-235. <https://doi.org/10.1016/j.buildenv.2014.02.005>
- [97] Cao, J., Ding, W.Y., Zhao, D.S. and Liu, H.M. (2014) Time Series Forecast of Foundation Pit Deformation Based on BP Neural Network. *Applied Mechanics and Materials*, **556-562**, 5979-5983.
<https://doi.org/10.4028/www.scientific.net/AMM.556-562.5979>
- [98] Ma, F., Zheng, Y. and Yang, F. (2008) Research on Deformation Prediction Method of Soft Soil Deep Foundation Pit. *Journal of Coal Science and Engineering (China)*, **14**, 637-639. <https://doi.org/10.1007/s12404-008-0430-5>
- [99] Zhang, L., Wu, X., Skibniewski, M.J., *et al.* (2014) Bayesian-Network-Based Safety Risk Analysis in Construction Projects. *Reliability Engineering & System Safety*, **131**, 29-39. <https://doi.org/10.1016/j.res.2014.06.006>
- [100] Zhou, Y., Li, C., Zhou, C. and Luo, H. (2018) Using Bayesian Network for Safety Risk Analysis of Diaphragm Wall Deflection Based on Field Data. *Reliability Engineering & System Safety*, **180**, 152-167. <https://doi.org/10.1016/j.res.2018.07.014>
- [101] Chang, F., Guo, C.-Y., Lin, X.-R., *et al.* (2010) Tree Decomposition for Large-Scale SVM Problems. 2010 *International Conference on Technologies and Applications of Artificial Intelligence*, Hsinchu, 18-20 November 2010, 233-240.
<https://doi.org/10.1109/TAAL.2010.47>
- [102] Das, S.K., Samui, P. and Sabat, A.K. (2012) Prediction of Field Hydraulic Conductivity of Clay Liners Using an Artificial Neural Network and Support Vector Machine. *International Journal of Geomechanics*, **12**, 606-611.
[https://doi.org/10.1061/\(ASCE\)GM.1943-5622.0000129](https://doi.org/10.1061/(ASCE)GM.1943-5622.0000129)
- [103] Tan, G.J., Liu, Ha.B., Cheng, Y.C., *et al.* (2011) Prediction Method for the Deformation of Deep Foundation Pit Based on Neural Network Algorithm Optimized by Particle Swarm. *Proceedings 2011 International Conference on Transportation, Mechanical, and Electrical Engineering (TMEE)*, Changchun, 16-18 December 2011, 1407-1410.
- [104] Zhao, F., Chen, C. and Qian, F. (2015) Analysis of Neural Network Models in Prediction of Ground Surface Settlement around Deep Foundation Pit. *Proceedings of the 2015 International Conference on Architectural, Civil and Hydraulics Engineering*, Guangzhou City, 28-29 November 2015, 418-424.
<https://doi.org/10.2991/icache-15.2015.81>
- [105] Breiman, L. (2001) Random Forests. *Machine Learning*, **45**, 5-32.
<https://doi.org/10.1023/A:1010933404324>
- [106] Hong, H., Tsangaratos, P., Ilia, I., *et al.* (2017) Comparing the Performance of a Logistic Regression and a Random Forest Model in Landslide Susceptibility Assess-

- ments. The Case of Wuyaun Area, China. In: Mikos, M., Tiwari, B., Yin, Y. and Sassa, K., Eds., *Advancing Culture of Living with Landslides*, Springer International Publishing, Cham, 1043-1050. https://doi.org/10.1007/978-3-319-53498-5_118
- [107] Zhou, J., Shi, X., Du, K., *et al.* (2017) Feasibility of Random-Forest Approach for Prediction of Ground Settlements Induced by the Construction of a Shield-Driven Tunnel. *International Journal of Geomechanics*, **17**, Article ID: 04016129. [https://doi.org/10.1061/\(ASCE\)GM.1943-5622.0000817](https://doi.org/10.1061/(ASCE)GM.1943-5622.0000817)
- [108] Zhou, Y., Li, S., Zhou, C. and Luo, H. (2019) Intelligent Approach Based on Random Forest for Safety Risk Prediction of Deep Foundation Pit in Subway Stations. *Journal of Computing in Civil Engineering*, **33**, Article ID: 05018004. [https://doi.org/10.1061/\(ASCE\)CP.1943-5487.0000796](https://doi.org/10.1061/(ASCE)CP.1943-5487.0000796)
- [109] Van Der Krogt, M.G., Schweckendiek, T. and Kok, M. (2019) Uncertainty in Spatial Average Undrained Shear Strength with a Site-Specific Transformation Model. *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, **13**, 226-236. <https://doi.org/10.1080/17499518.2018.1554820>
- [110] Brown, E.T. (2012) Risk Assessment and Management in Underground Rock Engineering—An Overview. *Journal of Rock Mechanics and Geotechnical Engineering*, **4**, 193-204. <https://doi.org/10.3724/SP.J.1235.2012.00193>
- [111] Phoon, K.K. and Ching, J. (2015) *Risk and Reliability in Geotechnical Engineering*. CRC Press/Spon, Boca Raton, FL.
- [112] Beer, M., Zhang, Y., Quek, S.T. and Phoon, K.K. (2013) Reliability Analysis with Scarce Information: Comparing Alternative Approaches in a Geotechnical Engineering Context. *Structural Safety*, **41**, 1-10. <https://doi.org/10.1016/j.strusafe.2012.10.003>
- [113] Chakraborty, M., Krishna, A.M. and Chakraborty, A. (2011) Reliability Based Performance Evaluation of Earth Retaining Structures. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 762-769. [https://doi.org/10.1061/41183\(418\)79](https://doi.org/10.1061/41183(418)79)
- [114] Fenton, G.A., Naghibi, F. and Griffiths, D.V. (2016) On a Unified Theory for Reliability-Based Geotechnical Design. *Computers and Geotechnics*, **78**, 110-122. <https://doi.org/10.1016/j.compgeo.2016.04.013>
- [115] Sekhvatian, A. and Choobbasti, A.J. (2018) Reliability Analysis of Deep Excavations by RS and MCS Methods: Case Study. *Innovative Infrastructure Solutions*, **3**, Article No. 60. <https://doi.org/10.1007/s41062-018-0166-z>
- [116] Daoulas, J.C. (2011) Georisk in the Design-Build Procurement Process. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 1090-1097. [https://doi.org/10.1061/41183\(418\)119](https://doi.org/10.1061/41183(418)119)
- [117] Lach, M.A. (2011) Managing Settlement Risk Due to Tunneling Beneath Downtown Seattle. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 996-1003. [https://doi.org/10.1061/41183\(418\)108](https://doi.org/10.1061/41183(418)108)
- [118] Park, J.K., Biscontin, G. and Gardoni, P. (2011) Reliability Analysis of Deep Excavation Based on a Semi-Empirical Approach. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 568-577. [https://doi.org/10.1061/41183\(418\)56](https://doi.org/10.1061/41183(418)56)
- [119] Tang, Y.G. and Kung, G.T.C. (2011) Probabilistic Analysis of Basal Heave in Deep Excavation. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 217-224. [https://doi.org/10.1061/41183\(418\)13](https://doi.org/10.1061/41183(418)13)
- [120] Naghibi, F., Fenton, G.A. and Griffiths, D.V. (2016) Probabilistic Considerations for

- the Design of Deep Foundations against Excessive Differential Settlement. *Canadian Geotechnical Journal*, **53**, 1167-1175. <https://doi.org/10.1139/cgj-2015-0194>
- [121] Christian, J.T. and Baecher, G.B. (2011) Unresolved Problems in Geotechnical Risk and Reliability. *GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 50-63. [https://doi.org/10.1061/41183\(418\)3](https://doi.org/10.1061/41183(418)3)
- [122] Sartain, N., Mian, J. and Peluso, D. (2017) Risk Assessment in Geotechnical Engineering Practice. *Geo-Risk 2017: Geotechnical Risk Assessment and Management*, Denver, 4-7 June 2017, 299-311. <https://doi.org/10.1061/9780784480731.024>
- [123] Fenton, G.A. (2013) Geotechnical Design Code Development in Canada. In: Arnold, P., Fenton, G.A., Hicks, M.A., et al., Eds., *Modern Geotechnical Design Codes of Practice*, IOS Press, Amsterdam, 277-294.
- [124] Fenton, G.A. and Naghibi, F. (2014) Reliability-Based Geotechnical Design Code Development. *2nd International Conference on Vulnerability and Risk Analysis and Management (ICVRAM) and the 6th International Symposium on Uncertainty, Modeling, and Analysis (ISUMA)*, Liverpool, 13-16 July 2014, 2468-2477. <https://doi.org/10.1061/9780784413609.248>
- [125] Korff, M. and Frits Van, T.A. (2013) Failure Cost Analysis of 50 Deep Excavations in the Netherlands. *Forensic Engineering: Informing the Future with Lessons from the Past*, London, 16-17 April 2013, 215-224.
- [126] Phoon, K.-K. (2020) The Story of Statistics in Geotechnical Engineering. *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, **14**, 3-25. <https://doi.org/10.1080/17499518.2019.1700423>
- [127] Lu, Y. and Tan, Y. (2019) Overview of Typical Excavation Failures in China. *Geo-Congress 2019*, Philadelphia, 24-27 March 2019, 315-332. <https://doi.org/10.1061/9780784482155.033>
- [128] Peck, R.B. (1969) Deep Excavations and Tunneling in Soft Ground. *Proceedings of the 7th International Conference on Soil Mechanics and Foundation Engineering*, Mexico, 225-290.
- [129] Abdrabbo, F.M. and Gaaver, K.E. (2012) Application of the Observational Method in Deep Foundation. *Alexandria Engineering Journal*, **51**, 269-279. <https://doi.org/10.1016/j.aej.2012.10.004>
- [130] Marr, W.A. and Hawkes, M. (2010) Displacement-Based Design for Deep Excavations. *Proceedings of the 2010 Earth Retention Conference*, Bellevue, 1-4 August 2010, 82-100. [https://doi.org/10.1061/41128\(384\)6](https://doi.org/10.1061/41128(384)6)
- [131] Powderham, A.J. (2002) The Observational Method—Learning from Projects. *Proceedings of the Institution of Civil Engineers-Geotechnical Engineering*, **155**, 59-69. <https://doi.org/10.1680/geng.2002.155.1.59>
- [132] Spross, J. and Johansson, F. (2017) When Is the Observational Method in Geotechnical Engineering Favorable. *Structural Safety*, **66**, 17-26. <https://doi.org/10.1016/j.strusafe.2017.01.006>
- [133] Górska, K., Muszyński, Z. and Rybak, J. (2013) Displacement Monitoring and Sensitivity Analysis in the Observational Method. *Studia Geotechnica et Mechanica*, **35**, 25-43. <https://doi.org/10.2478/sgem-2013-0028>
- [134] Hardy, S., Nicholson, D., Ingram, P., et al. (2017) New Observational Method Framework and Application. *Proceedings of the 19th International Conference on Soil Mechanics and Geotechnical Engineering*, Seoul, 17-21 September 2017, 1995-1998.
- [135] D'Appolonia, E. (1990) Monitored Decisions. *Journal of Geotechnical Engineering*, **116**, 4-34. [https://doi.org/10.1061/\(ASCE\)0733-9410\(1990\)116:1\(4\)](https://doi.org/10.1061/(ASCE)0733-9410(1990)116:1(4))

- [136] Whitman, R.V. (1984) Evaluating Calculated Risk in Geotechnical Engineering. *Journal of Geotechnical Engineering*, **110**, 143-188. [https://doi.org/10.1061/\(ASCE\)0733-9410\(1984\)110:2\(143\)](https://doi.org/10.1061/(ASCE)0733-9410(1984)110:2(143))
- [137] Finno, R.J. (2007) Use of Monitoring Data to Update Performance Predictions of Supported Excavations. *Proceedings of the 7th International Symposium on Field Measurements in Geomechanics*, Boston, 24-27 September 2007, 1-30. [https://doi.org/10.1061/40940\(307\)3](https://doi.org/10.1061/40940(307)3)
- [138] Young, D.K. and Ho, E.W.L. (1994) The Observational Approach to Design of a Sheet-Piled Retaining Wall. *Géotechnique*, **44**, 637-654. <https://doi.org/10.1680/geot.1994.44.4.637>
- [139] Ikuta, Y., Maruoka, M., Aoki, M. and Sato, E. (1994) Application of the Observational Method to a Deep Basement Excavated Using the Top-Down Method. *Géotechnique*, **44**, 655-679. <https://doi.org/10.1680/geot.1994.44.4.655>
- [140] Fuentes, R., Pillai, A. and Ferreira, P. (2018) Lessons Learnt from a Deep Excavation for Future Application of the Observational Method. *Journal of Rock Mechanics and Geotechnical Engineering*, **10**, 468-485. <https://doi.org/10.1016/j.jrmge.2017.12.004>
- [141] Wu, S.-H., Ching, J. and Ou, C.-Y. (2014) Probabilistic Observational Method for Estimating Wall Displacements in Excavations. *Canadian Geotechnical Journal*, **51**, 1111-1122. <https://doi.org/10.1139/cgj-2013-0116>
- [142] Finno, R.J. and Calvello, M. (2005) Supported Excavations: Observational Method and inverse Modeling. *Journal of Geotechnical and Geoenvironmental Engineering*, **131**, 826-836. [https://doi.org/10.1061/\(ASCE\)1090-0241\(2005\)131:7\(826\)](https://doi.org/10.1061/(ASCE)1090-0241(2005)131:7(826))
- [143] Calvello, M. (2017) from the Observational Method to “Observational Modelling” of Geotechnical Engineering Boundary Value Problems. *Geotechnical Safety and Reliability*, Denver, 4-7 June 2017, 101-117. <https://doi.org/10.1061/9780784480731.008>
- [144] Calvello, M. and Finno, R.J. (2003) Modeling Excavations in Urban Areas: Effects of Past Activities. *Rivista Italiana di Geotecnica*, **37**, 9-23.
- [145] Scott, P. (2019) Advanced Geotechnical Education and Acquiring Good Engineering Judgment through Project Experiences. *8th International Conference on Case Histories in Geotechnical Engineering*, Philadelphia, 24-27 March 2019, 59-72. <https://doi.org/10.1061/9780784482162.006>
- [146] Allen, M., Gaura, E., Wilkins, R., *et al.* (2017) Proof of Concept of Wireless TERS Monitoring. *Structural Control and Health Monitoring*, **24**, e2026. <https://doi.org/10.1002/stc.2026>
- [147] He, W., Duan, Y., Deng, L. and Zhou, W. (2016) Risk Assessment and Early-Warning System for High-Speed Railway during the Construction and Operation of Underpass Bridges. *Journal of Performance of Constructed Facilities*, **30**, C4015003. [https://doi.org/10.1061/\(ASCE\)CF.1943-5509.0000717](https://doi.org/10.1061/(ASCE)CF.1943-5509.0000717)
- [148] Kanan, R., Elhassan, O. and Bensalem, R. (2018) An IoT-Based Autonomous System for Workers’ Safety in Construction Sites with Real-Time Alarming, Monitoring, and Positioning Strategies. *Automation in Construction*, **88**, 73-86. <https://doi.org/10.1016/j.autcon.2017.12.033>
- [149] Teizer, J., Allread, B.S., Fullerton, C.E. and Hinze, J. (2010) Autonomous Pro-Active Real-Time Construction Worker and Equipment Operator Proximity Safety Alert System. *Automation in Construction*, **19**, 630-640. <https://doi.org/10.1016/j.autcon.2010.02.009>

- [150] Liu, J., Ren, F. and Liu, Y. (2011) Research on Monitoring-Based Risk Management of Deep Excavation Engineering. 2011 *International Conference on Management and Service Science*, Wuhan, 12-14 August 2011, 1-4. <https://doi.org/10.1109/ICMSS.2011.5998174>
- [151] Hayati, M. and Abroshan, M.R. (2017) Risk Assessment Using Fuzzy FMEA (Case Study: Tehran Subway Tunneling Operations). *Indian Journal of Science and Technology*, **10**, 1-9. <https://doi.org/10.17485/ijst/2017/v10i9/110157>
- [152] Li, M., Yu, H. and Liu, P. (2018) An Automated Safety Risk Recognition Mechanism for Underground Construction at the Pre-Construction Stage Based on BIM. *Automation in Construction*, **91**, 284-292. <https://doi.org/10.1016/j.autcon.2018.03.013>
- [153] Sacks, R., Eastman, C., Lee, G. and Teicholz, P. (2018) BIM Handbook: A Guide to Building Information Modeling for Owners, Designers, Engineers, Contractors, and Facility Managers. John Wiley & Sons, Inc., Hoboken. <https://doi.org/10.1002/9781119287568>
- [154] Martínez-Aires, M.D., López-Alonso, M. and Martínez-Rojas, M. (2018) Building Information Modeling and Safety Management: A Systematic Review. *Safety Science*, **101**, 11-18. <https://doi.org/10.1016/j.ssci.2017.08.015>
- [155] Zhou, Y., Ding, L.Y. and Chen, L.J. (2013) Application of 4D Visualization Technology for Safety Management in Metro Construction. *Automation in Construction*, **34**, 25-36. <https://doi.org/10.1016/j.autcon.2012.10.011>
- [156] Kanan, R., Elhassan, O., Bensalem, R. and Husein, A. (2016) A Wireless Safety Detection Sensor System. 2016 *IEEE SENSORS*, Orlando, 30 October-3 November 2016, 1-3. <https://doi.org/10.1109/ICSENS.2016.7808926>
- [157] Marks, E.D. and Teizer, J. (2013) Method for Testing Proximity Detection and Alert Technology for Safe Construction Equipment Operation. *Construction Management and Economics*, **31**, 636-646. <https://doi.org/10.1080/01446193.2013.783705>
- [158] Skibniewski, M. (2014) Research Trends in Information Technology Applications in Construction Safety Engineering and Management. *Frontiers of Engineering Management*, **1**, 246-259. <https://doi.org/10.15302/J-FEM-2014034>
- [159] Yuan, W., Songyu, L., Jianyong, L., *et al.* (2010) Deep Foundation Pit Construction Monitoring Information System Based on GIS. IOS Press, Amsterdam, 361-367.
- [160] Tinghua, X., Siping, B. and Jingru, C. (2008) Safety Management of Deep Foundation Pit Based on Construction Risk Analysis. 2008 *ISECS International Colloquium on Computing, Communication, Control, and Management*, Guangzhou, 3-4 August 2008, 268-272. <https://doi.org/10.1109/CCCM.2008.63>
- [161] Zhang, Y. and Guan, X. (2018) Selecting Project Risk Preventive and Protective Strategies Based on Bow-Tie Analysis. *Journal of Management in Engineering*, **34**, Article ID: 04018009. [https://doi.org/10.1061/\(ASCE\)ME.1943-5479.0000603](https://doi.org/10.1061/(ASCE)ME.1943-5479.0000603)
- [162] Ahuja, H.N., Dozzi, S.P. and Abourizk, S.M. (1994) Project Management: Techniques in Planning and Controlling Construction Projects. 2nd Edition, Wiley, New York.
- [163] Goh, A.T.C., Wong, K.S., Teh, C.I. and Wen, D. (2003) Pile Response Adjacent to Braced Excavation. *Journal of Geotechnical and Geoenvironmental Engineering*, **129**, 383-386. [https://doi.org/10.1061/\(ASCE\)1090-0241\(2003\)129:4\(383\)](https://doi.org/10.1061/(ASCE)1090-0241(2003)129:4(383))
- [164] Poulos, H.G. (2007) Ground Movements—A Hidden Source of Loading on Deep Foundations. *DFI Journal—The Journal of the Deep Foundations Institute*, **1**, 37-53. <https://doi.org/10.1179/dfi.2007.004>

- [165]Pham, Q.N., Ohtsuka, S., Isobe, K. and Fukumoto, Y. (2019) Group Effect on Ultimate Lateral Resistance of Piles against Uniform Ground Movement. *Soils and Foundations*, **59**, 27-40. <https://doi.org/10.1016/j.sandf.2018.08.013>
- [166]Katzenbach, R., Leppla, S., Ramm, H., *et al.* (2013) Design and Construction of Deep Foundation Systems and Retaining Structures in Urban Areas in Difficult Soil and Groundwater Conditions. *Procedia Engineering*, **57**, 540-548. <https://doi.org/10.1016/j.proeng.2013.04.069>
- [167]Rolf, K., Steffen, L. and Matthias, S. (2015) Risk Management and Risk Communication in Geotechnical Engineering by Independent Peer Review and Special Technical Solutions. IOS Press, Amsterdam, 76-87.
- [168]Saeedi Azizkandi, A.R., Taherkhani, R. and Taji, A. (2019) Experimental Study of a Square Foundation with Connected and Non-Connected Piled Raft Foundation under Eccentrically Loaded. *Civil Engineering Infrastructures Journal*, **52**, 185-203.
- [169]Ata, A., Badrawi, E. and Nabil, M. (2015) Numerical Analysis of Unconnected Piled Raft with Cushion. *Ain Shams Engineering Journal*, **6**, 421-428. <https://doi.org/10.1016/j.asej.2014.11.002>
- [170]El Sawwaf, M. (2010) Experimental Study of Eccentrically Loaded Raft with Connected and Unconnected Short Piles. *Journal of Geotechnical and Geoenvironmental Engineering*, **136**, 1394-1402. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0000341](https://doi.org/10.1061/(ASCE)GT.1943-5606.0000341)
- [171]Fioravante, V. and Giretti, D. (2010) Contact versus Noncontact Piled Raft Foundations. *Canadian Geotechnical Journal*, **47**, 1271-1287. <https://doi.org/10.1139/T10-021>
- [172]Mattsson, N., Menoret, A., Simon, C. and Ray, M. (2013) Case Study of a Full-Scale Load Test of a Piled Raft with an Interposed Layer for a Nuclear Storage Facility. *Géotechnique*, **63**, 965-976. <https://doi.org/10.1680/geot.12.P.166>
- [173]Zhu, X., Fei, K. and Wang, S. (2018) Horizontal Loading Tests on Disconnected Piled Rafts and a Simplified Method to Evaluate the Horizontal Bearing Capacity. *Advances in Civil Engineering*, **2018**, Article ID: 3956509. <https://doi.org/10.1155/2018/3956509>
- [174]Azizkandi, A.S., Baziar, M.H. and Yeznabad, A.F. (2018) 3D Dynamic Finite Element Analyses and 1 G Shaking Table Tests on Seismic Performance of Connected and Nonconnected Piled Raft Foundations. *KSCE Journal of Civil Engineering*, **22**, 1750-1762. <https://doi.org/10.1007/s12205-017-0379-2>
- [175]Suleiman, M.T., Ni, L., Helm, J.D. and Raich, A. (2014) Soil-Pile Interaction for a Small Diameter Pile Embedded in Granular Soil Subjected to Passive Loading. *Journal of Geotechnical and Geoenvironmental Engineering*, **140**, Article ID: 04014002. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0001081](https://doi.org/10.1061/(ASCE)GT.1943-5606.0001081)
- [176]Ashford, S.A., Juirnarongrit, T., Sugano, T. and Hamada, M. (2006) Soil-Pile Response to Blast-Induced Lateral Spreading. I: Field Test. *Journal of Geotechnical and Geoenvironmental Engineering*, **132**, 152-162. [https://doi.org/10.1061/\(ASCE\)1090-0241\(2006\)132:2\(152\)](https://doi.org/10.1061/(ASCE)1090-0241(2006)132:2(152))
- [177]Wang, G. and Yang, Y. (2013) Effect of Cantilever Soldier Pile Foundation Excavation Closing to an Existing Composite Foundation. *Journal of Central South University*, **20**, 1384-1396. <https://doi.org/10.1007/s11771-013-1626-4>
- [178]Li, L., Huang, J. and Han, B. (2018) Centrifugal Investigation of Excavation Adjacent to Existing Composite Foundation. *Journal of Performance of Constructed Facilities*, **32**, Article ID: 04018044.

[https://doi.org/10.1061/\(ASCE\)CF.1943-5509.0001188](https://doi.org/10.1061/(ASCE)CF.1943-5509.0001188)

- [179] Wei, Y. (2018) Research on Evolutionary Mechanisms and Calculation Method of Earth Pressure against Rigid Retaining Walls Close to Rigid Composite Foundation. PhD Dissertation, Zhengzhou University, Zhengzhou.
- [180] Ren, G.F. and Qiao, J.S. (2013) Research on the Mechanical Behavior Effect of around Composite Foundation under Soil Lateral Displacement. *Applied Mechanics and Materials*, 353-356, 696-701.
<https://doi.org/10.4028/www.scientific.net/AMM.353-356.696>
- [181] Zhang, R., Zhang, W. and Goh, A.T.C. (2018) Numerical Investigation of Pile Responses Caused by Adjacent Braced Excavation in Soft Clays. *International Journal of Geotechnical Engineering*, 1-15. <https://doi.org/10.1080/19386362.2018.1515810>
- [182] Bilotta, E. and Russo, G. (2011) Use of a Line of Piles to Prevent Damages Induced by Tunnel Excavation. *Journal of Geotechnical and Geoenvironmental Engineering*, **137**, 254-262. [https://doi.org/10.1061/\(ASCE\)GT.1943-5606.0000426](https://doi.org/10.1061/(ASCE)GT.1943-5606.0000426)
- [183] Leung, C.F., Lim, J.K., Shen, R.F. and Chow, Y.K. (2003) Behavior of Pile Groups Subject to Excavation-Induced Soil Movement. *Journal of Geotechnical and Geoenvironmental Engineering*, **129**, 58-65.
[https://doi.org/10.1061/\(ASCE\)1090-0241\(2003\)129:1\(58\)](https://doi.org/10.1061/(ASCE)1090-0241(2003)129:1(58))
- [184] Luo, Z., Juang, C.H. and Huang, F.-K. (2011) Wall and Ground Responses in a Braced Excavation Considering Spatial Variability. *Proceedings of GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 770-777.
[https://doi.org/10.1061/41183\(418\)80](https://doi.org/10.1061/41183(418)80)
- [185] Marr, W.A. (2011) Active Risk Management in Geotechnical Engineering. *Proceedings of GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 894-901. [https://doi.org/10.1061/41183\(418\)95](https://doi.org/10.1061/41183(418)95)
- [186] Pennington, T.W. and Richards, D.P. (2011) Understanding Uncertainty: Assessment and Management of Geotechnical Risk in Tunnel Construction. *Proceedings of GeoRisk 2011: Geotechnical Risk Assessment and Management*, Atlanta, 26-28 June 2011, 552-559. [https://doi.org/10.1061/41183\(418\)54](https://doi.org/10.1061/41183(418)54)
- [187] Fok, P., Neo, B.H., Wen, D. and Veeresh, C. (2012) Design and Construction of Earth Retaining Walls for Deep Excavation—A Risk Management Process. *The IES Journal Part A: Civil & Structural Engineering*, **5**, 204-209.
<https://doi.org/10.1080/19373260.2012.696441>
- [188] Spross, J., Olsson, L. and Stille, H. (2018) The Swedish Geotechnical Society's Methodology for Risk Management: A Tool for Engineers in Their Everyday Work. *Georisk: Assessment and Management of Risk for Engineered Systems and Geohazards*, **12**, 183-189. <https://doi.org/10.1080/17499518.2017.1416643>
- [189] Choi, H.-H., Cho, H.-N. and Seo, J.W. (2004) Risk Assessment Methodology for Underground Construction Projects. *Journal of Construction Engineering and Management*, **130**, 258-272.
[https://doi.org/10.1061/\(ASCE\)0733-9364\(2004\)130:2\(258\)](https://doi.org/10.1061/(ASCE)0733-9364(2004)130:2(258))
- [190] O'Neil, C. (2018) Effective Risk Management Processes. *Global Construction Success*. John Wiley & Sons, Inc., Chichester, 177-187.
<https://doi.org/10.1002/9781119440345.ch17>
- [191] Xiong, Z., Lu, H., Wang, M., et al. (2018) Research Progress on Safety Risk Management for Large Scale Geotechnical Engineering Construction in China. *Rock and Soil Mechanics*, **39**, 3703-3716.

- [192] Bai, Y., Dai, Z. and Zhu, W. (2014) Multiphase Risk-Management Method and Its Application in Tunnel Engineering. *Natural Hazards Review*, **15**, 140-149.
[https://doi.org/10.1061/\(ASCE\)NH.1527-6996.0000124](https://doi.org/10.1061/(ASCE)NH.1527-6996.0000124)
- [193] Cárdenas, I.C., Al-Jibouri, S.S.H., Halman, J.I.M., *et al.* (2014) Using Prior Risk-Related Knowledge to Support Risk Management Decisions: Lessons Learnt from a Tunneling Project: Using Prior Risk-Related Knowledge to Support Risk Management Decisions. *Risk Analysis*, **34**, 1923-1943.
<https://doi.org/10.1111/risa.12213>